

# ENDO-ONE VISION 4K PRIDE

Professional 4K Video Recorder

**4K 30**  
HDMI pass-through  
4K30 Capture



## Features

- HDMI 2.0 pass-through, comply with HDCP 2.2
- Support most of video sources having HDMI / DVI output (like: Medical Devices, Game Consoles, STB, Receivers, OTT Boxes etc).
- Capture same video resolutions as input :  
UHD : 4K30, 4K25, 4K24  
FHD : 1080p60/p50/p30/p25/p24, 1080i60, 1080i50  
HD : 720p60, 720p50  
SD : 576p50, 480p60, 576i50, 480i60
- Capture format : H.264 High profile / H.265 main profile, AAC/MP4
- Sampling rate : 48kHz PCM
- Bitrate in H.264 recording :  
UHD 16Mbps, FHD 12Mbps, HD 8Mbps, SD 4Mbps.  
Bitrate in H.265 recording :  
UHD 12Mbps, FHD & HD 8Mbps, SD 4Mbps.
- 3.5mm Microphone input, can record your voice during video recording.
- Screenshot format : JPG
- Instant Playback & Pre-set schedule recording.
- OSD control with multi-languages.
- Snapshot via remote control (IR)



TIME  
WATER MARK



BITRATE  
SELECTION



REMOTE  
CONTROL



SCHEDULE  
RECORDING



RECORDING  
& PLAYBACK



SEGMENT SIZE  
SELECTION



SNAPSHOT



IN/OUT



H.264/  
H.265  
CAPTURE  
FORMAT



MIC  
IN/OUT



HARD DISK  
MAX. 4TB



MAX. 128 GB



## Input / Output Connectors

- HDMI In & Out (HDMI 2.0)
- Line In & Line Out
- MIC (3.5mm audio jack)
- USB Type A (for storage)
- Micro USB (for PC)

## Storage Device

- USB flash drive Max. 128GB; USB HDD Max. 4TB
- Supported Storage Format : FAT32, NTFS, exFAT
- File Size : FAT32: 4G/file; NTFS & exFAT: 32GB/file

## Mechanical

- Dimension : 131x85x24mm  
 (5.16"x3.35"x0.94")
- Weight : 580g
- Environment Operating Temp.: 0~50°C
- Storage Temp. : Temp.-20°C to 60°C
- Humidity : 10 to 85%
- Certification : CE/FCC

## Package Contents

- 4K Video Recorder
- Remote control
- HDMI 2.0 cable
- DVI male to HDMI male cable
- Power adapter 5V/2A
- Quick Start Guide



**Connection Diagram**