

All-in-One FHD Video Recorder



ENDO-ONE VISION HD FUSION



FEATURES

- Built-in 7" LCD screen, offering real-time monitoring & playback
- No Computer, no drivers and no special software is required
- Support most of 4K, FHD, HD & SD video sources
- One click recording, one click stop
- Multiple video input : HDMI, SDI, DVI, S-Video, MMI Cable (VGA, YPbPr, RCA)
- MIC input, Line input (audio overlap),
- Line output (headphones / speaker), Foot Pedal input
- HDMI pass-through without latency (up to 1080P60)
- Support Foot Pedal control for Recording & Snapshot



- Capture resolution up to 1080p60
- Storage can be SD card, USB, or Hard disk.
- The device saves videos in H.264 (MP4) format
- Enable loop recording
- Support Remote control (IR) and external battery backup
- Instant Playback & pre-set schedule recording
- Capture images during video recording



Support Standalone Recorder

SD card Slot*1 : SD (FAT32, NTFS, exFAT Max. 512 GB)

USB Type A*1 : USB Flash Drive Max 512 GB, Hard Disk Max 8TB (FAT32, NTFS, exFAT, GPT, MBR)

HDD : GPT, MBR Max. 8TB

Mkt. by :



swift MEDI ELEC SOLUTIONS

10/812-B, SHIVANAND NAGAR, SECTOR- 3, RAIPUR- 492008 (CHHATTISGARH)

☎ : +91-98261 71056 E-mail : swift.mes@gmail.com Website : www.swiftmedi.co.in

All-in-One FHD Video Recorder



ENDO-ONE

VISION HD FUSION



The device does not contain a built-in battery.
External battery sold separately

Compatible models : Sony NP-F550, F750, and F970 7.4V.

A CR2032 battery is included with the device to preserve the time & date setting.



EXT. BATTERY



512 GB



SEGMENT SIZE



SNAPSHOT



HARD DISK
8 TB



SD CARD
512 GB



REMOTE
CONTROL



SCHEDULE
RECORDING



MIC
IN/OUT



PICTURE
QUALITY

HDMI / SDI/ DVI/ VGA/ Component (YPBPR)/ Composite (AV)/ S-VIDEO Video input supports		4K2K (3840x2160 30p), 1920x1080 (60p, 50p, 25p, 24p,30p, 60i, 50i), 1360x768 (60p), 1280x1024 (60p), 1280x720 (60p), 1280x768 (60P), 1280x800 (60p), 1024x768 (60p), 720x480 (60p, 60i, 50i), 640x480(60p), 720x576 (50p)
Record Resolution		1920x1080 (60p), 1280x720 (60p), 1024x768 (60p), 1280x800 (60p)
Input / Output Interface	Input	HDMI in, SDI in, DVI in, S-Video in, MMI in (YPBPR, VGA, RCA) MIC in, LINE in, Power in (12V/1.5A). Foot (Foot Pedal for recorder or snapshot)
	Output	HDMI out Line out, SD card slot : SD (FAT32, NTFS, exFAT Max. 512GB) USB Type A x 1: Flash Drive Max. 512 GB, Hard Disk (FAT32, NTFS, exFAT Max 8 TB) HDD Slot : GPT, MBR Max. 8 TB
Adapter Voltage		Input 100~240V 50/60Hz, Output 12V/1.5A
Working temperature		0 to 50°C
Power consumption		Less than 18W
Reserve temperature		-20 to +60°C

